

"Express Mail" mailing label number ER 160260164 US

PATENT APPLICATION
DOCKET NO. 10012147-4

METHODS AND APPARATUS FOR SCORING AND TRIMMING
IMAGED SHEET MEDIA

INVENTOR:

Roland Boss

1 **METHODS AND APPARATUS FOR SCORING AND TRIMMING**
2 **IMAGED SHEET MEDIA**

3
4 **FIELD OF THE INVENTION**

5 The invention claimed and disclosed herein pertains to methods and apparatus
6 for folding and/or trimming a sheet of media, such as paper, in a document production
7 apparatus.

8
9 **BACKGROUND OF THE INVENTION**

10 Apparatus known as "document production apparatus" are generally configured
11 to process one or more sheets of media (such as paper) to thereby form the media into a
12 finished document. Some document processing apparatus can bind a plurality of sheets
13 into a single document. Other document production apparatus can include a sheet
14 folding device that can fold a sheet of media, such as paper, into a bi-fold, tri-fold, or
15 other multi-folded pamphlet. For example, Fig. 1 depicts a tri-fold pamphlet 10 formed
16 from a single sheet of media "M". The sheet "M" is folded along a first fold line 18 which
17 segregates the sheet "M" into portions 12 and 14. The sheet "M" is further folded along
18 a second fold line 20 which further segregates the sheet "M" into portions 14 and 16.
19 Document processing apparatus having sheet-folding capability are known in the art.
20 (See, for example, U.S. Patent No. 6,132,352, incorporated herein by reference.)

21 Also known are document production apparatus which incorporate a trimming or
22 cutting device which can cut or trim media to a desired size. (See, for example, U.S.
23 Patent Nos. 5,527,567 and 5,708,345, which are both incorporated herein by reference.)
24 Such trimming and cutting devices allow media to be provided from a continuous roll of
25 media, and also allow a document to be trimmed to a desired size after imaging.

1 Some prior art apparatus used to fold a sheet of media into a multi-fold pamphlet
2 typically incorporate a pinch bar or pinch roller (a "pinch device") which urges a portion
3 of the sheet, along which a fold is to be formed, towards a pair of counter-rotating fold-
4 forming rollers. For purposes of the following discussion, I will define the line along
5 which a fold is to be formed in a sheet of media as the "intended fold line", and the line
6 along which the actual fold is formed as the "fold line". The counter-rotating rollers,
7 which are preferably in contact with one another and are aligned along parallel axes,
8 then engage the sheet in the area of the intended fold line. The area in which the
9 counter-rotating rollers (the "fold rollers") engage the sheet is known as the "nip". As the
10 sheet passes through the fold rollers, the sheet is folded along the fold line. The sheet
11 can then be passed through another set of fold rollers, or passed back through the
12 original set of fold rollers, to form additional folds in the sheet. This is graphically
13 demonstrated in Fig. 2, which shows a side elevation view of a sheet of media "M" being
14 folded into leaves 31 and 33. The actual fold line will generally be located in the area
15 38. A pinch roller 30 moves in direction "A" to move the fold area 38 towards the nip 36
16 and into the counter-rotating fold rollers 32 and 34. The fold rollers 32 and 34 grasp the
17 sheet "M" as it is urged into the rollers, and thereby folds the sheet "M" into a bi-fold
18 sheet.

19 Such prior art apparatus sheet folding apparatus present several deficiencies.
20 First, the pinch bar does precisely direct the intended fold line towards the nip, but only
21 approximates the position of the intended fold line. This is demonstrated in Fig. 2, where
22 the actual fold line will be formed in the fold area 38, but is not clearly defined in this fold
23 area. As a result, the actual fold can be formed in a slightly different location on the
24 sheet than the desired fold line. In addition to the actual fold line not being coincident
25 with the intended fold line, the actual fold line can also be skewed with respect to the
26 intended fold line. This is demonstrated in Fig. 3, which shows a sheet of media "M"

1 which is intended to be folded into two equal parts along the intended fold line 44, but in
2 fact is folded along the actual fold 42, which is offset at a slight angle to the intended fold
3 line 44. The result it that when the first half 46 of the sheet "M" is folded over the second
4 half 48 of the sheet, the first edge 31 will not align with the second edge 33, providing a
5 visually unattractive pamphlet.

6 In other prior art sheet folding apparatus, rather than use a pinch bar to move the
7 document into the fold rollers, a stop device is used to stop forward progress of the
8 sheet. Since the sheet is still being fed by feed rollers, the sheet will be caused to
9 buckle and move into the fold rollers. This results in the fold being formed along a rather
10 imprecise line, since the area where the sheet will buckle can vary with the sheet
11 thickness and other variables. Further, the use of a stop device generally limits the
12 thickness of sheet media which can be used to form the folded pamphlet, since relatively
13 thick sheets will tend to crumple rather than buckle.

14 Another problem occurs when the fold line passes through an image (such as
15 text or graphics) on the sheet of media. In this event, folding the sheet along the fold
16 line can cause small portions of the image in the fold area to separate from the sheet.
17 This problem is particularly noted when the image is formed using a toner which is fused
18 to the sheet to create the image.

19 A further problem with prior art sheet folding apparatus is that they generally
20 require forward progress of the sheet media to be temporarily halted while the sheet
21 media is moved into the nip of the fold rollers. When the sheets to be folded are being
22 provided from an attached imaging device, this can determine the speed of the imaging
23 device, since the sheet folding device generally will not be able to process sheets of
24 media as quickly as the imaging device. Accordingly, anything which can be done to
25 improved the speed at which sheets of media can be folded by the sheet folding device

1 will generally allow the imaging device to operate closer to its design speed, thus
2 improving the speed of the overall imaging-folding process.

3 What is needed then is a document processing apparatus which achieves the
4 benefits to be derived from similar prior art devices, but which avoids the shortcomings
5 and detriments individually associated therewith.

6 7 SUMMARY OF THE INVENTION

8 One embodiment of the present invention includes a sheet finishing apparatus
9 having a media path configured to receive a sheet of media moving along the media
10 path. The apparatus includes a creasing tool disposed proximate the media path and
11 configured to form a crease in the sheet of media. The apparatus further includes a
12 sheet folding device configured to fold the sheet of media along the crease.

13 Another embodiment of the present invention includes a document processing
14 apparatus for folding or cutting a sheet of media. The apparatus includes a media path
15 configured to receive a sheet of media which moves along the media path. A first roller,
16 defined by a length and an outer surface, is disposed proximate the media path. The
17 first roller has an elongated slot formed therein along at least a portion of the length
18 parallel to axis of roller, and the slot opens to the outer surface of the roller. A knife,
19 defined by an edge, is received within the elongated slot in the roller. The knife is
20 configured to operably move from a first position wherein the edge of the knife is
21 retracted away from the surface of the roller, to a second position wherein the edge of
22 the knife protrudes outwardly from the surface of the roller. In the second position the
23 knife edge can thereby contact a sheet of media moving along the media path to thereby
24 either crease or cut the sheet.

25 A third embodiment of the present invention provides for a sheet finishing
26 apparatus, which is preferably configured to be used in conjunction with a sheet imaging

1 apparatus. The sheet finishing apparatus includes a media path configured to receive a
2 sheet of media from the imaging apparatus. A drive mechanism is configured to move a
3 sheet of media along the media path in a media path direction. An elongated member,
4 defined by an edge, is oriented perpendicular to the media path direction. The
5 elongated member is configured to operably move from a first position away from the
6 media path to a second position wherein the edge of the elongated member can contact
7 a sheet of media moving along the media path to thereby either crease or cut the sheet.

8 A fourth embodiment of the present invention provides for a method of folding a
9 sheet of media. The method includes providing a sheet of media, and automatically
10 forming a crease on the sheet of media. The crease is formed along a first crease line to
11 thereby define first and second portions of the sheet, each portion of the sheet being
12 defined by the first crease line. The sheet is then urged towards a nip by pressing the
13 sheet of media essentially along the crease while supporting the first and second
14 portions of the sheet. At the nip, the sheet is grasped at essentially the first crease line,
15 and the first portion of the sheet is urged towards the second portion of the sheet,
16 thereby forming a folded sheet of media.

17 These and other aspects and embodiments of the present invention will now be
18 described in detail with reference to the accompanying drawings, wherein:
19

20 DESCRIPTION OF THE DRAWINGS

21 Fig. 1 is an isometric diagram depicting a tri-fold pamphlet folded from a sheet of
22 media.

23 Fig. 2 is a side elevation schematic diagram depicting a sheet folding mechanism
24 of the prior art.

25 Fig. 3 is an isometric view of a sheet of media which is folded by an apparatus of
26 the prior art.

1 Fig. 4 is a side elevation diagram depicting a document processing apparatus in
2 accordance with one embodiment of the present invention.

3 Figs. 5A and 5B depict a side elevation sectional view of a roller in accordance
4 with the present invention which includes a knife to crease or cut a sheet of media,
5 showing the knife in two different positions.

6 Fig. 6A depicts a side elevation detail of rollers depicted in Fig. 4 which can be
7 used to crease or cut a first side of a sheet, in accordance with the present invention.

8 Fig. 6B depicts the rollers of Fig. 6A, but being used to crease or cut a second
9 side of a sheet.

10 Fig. 7 is a side elevation sectional view of the roller depicted in Fig. 5B.

11 Fig. 8 is a side elevation sectional view of a variation on the roller depicted in
12 Fig. 7.

13 Fig. 9 is a side elevation detail of a cutting and creasing anvil used in the roller of
14 Fig. 8.

15 Figs. 10A through 10J depict a series of steps that can be performed with the
16 apparatus of Fig. 4 to implement the methods of the present invention.

17 Fig. 11 depicts a flow chart of steps when can be executed to implement one
18 example of an embodiment of the present invention.

19 Fig. 12 depicts a side elevation view of a sheet of media being folded into a "Z"
20 shaped pamphlet.

21 Fig. 13 depicts a side elevation view of a sheet of media being folded into a first
22 form of a "U" shaped pamphlet.

23 Fig. 14 depicts a side elevation view of a sheet of media being folded into a
24 second form of a "U" shaped pamphlet.

25 Fig. 15 depicts a side elevation view of another configuration of scoring rollers
26 that can be used to implement the methods of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides methods and apparatus for processing a sheet of media. Specifically, the present invention can be used to facilitate folding of a sheet of media, and can also be used to cut or trim a sheet of media. By "sheet of media" I mean a sheet on which an image can be formed, as for example paper, a plastic transparency or cardstock. The present invention improves on prior art sheet folding methods and apparatus by forming a crease in the sheet at the intended fold position prior to folding the sheet. The crease allows the fold to be formed in a more precise location, and results in a visually more attractive fold over the prior art methods. Moreover, the sheet creasing and folding method of the present invention can be performed automatically, and can also be performed in-line, thus resulting in quicker processing of the sheet by an attached imaging device which feeds imaged sheets of media to the sheet folding device.

A first embodiment of the present invention is depicted in the side elevation schematic diagram of Fig. 4, which portrays a document processing apparatus 80 comprising an imaging apparatus 50 having an attached sheet finishing apparatus 100. The imaging apparatus 50 can be a printer or photocopier, for example. In the example shown, the imaging apparatus 50 is configured to move a sheet or media 52, such as a sheet of paper, along media path 53 and to the imaging section 54. The imaging section can be any known imaging section, such as an electrophotographic imaging section (commonly known as a "laser printer"), or an ink printing section, such as an ink-jet printer. The imaged media then is moved along media path 57 (using a drive mechanism such as powered rollers 55 or drive belts or the like) to the finishing section 100. The imaging apparatus 50 can include a processor 58 configured to control operation of the imaging apparatus 50, and can also be used to control operation of the sheet finishing section 100. A computer-readable memory device 59 can be provided to

1 allow a data file of an image, which is to be printed on the media, to be temporarily
2 stored, for example in the random access memory ("RAM") 60 portion of the memory
3 device 59. The memory device 59 can also be used to store a sheet folding/trimming
4 program 62, which can be used to control operation of the finishing section 100, as will
5 be described further below. The imaging apparatus can also be provided with a user
6 interface 64, which can include user input points (such as buttons or switches 65)
7 allowing a user to provide instructions to the processor 58 to direct the imaging
8 apparatus 50 to print images on sheets of media, and also to direct the finishing section
9 100 to apply finishing to the imaged media. The user interface 64 can also include a
10 display 66 to allow the processor 58 to communicate information to the user, such as
11 information regarding status of the imaging apparatus 50 and the finishing apparatus
12 100.

13 The sheet finishing apparatus 100 of the document processing apparatus 80 can
14 be configured to apply one or more of several finishing processes to imaged media. For
15 example, the finishing apparatus 100 can include a sheet binding device, such as a
16 stapler or a stitching device. However, for purposes of the present discussion, we will
17 assume that the sheet finishing apparatus includes only the sheet folding/trimming
18 apparatus of the present invention. As depicted in Fig. 4, the finishing apparatus 100
19 includes a media path guide 110 configured to receive a sheet of media "M" from the
20 imaging apparatus 50. The "media path", as I use the term herein, is not constrained to
21 physical guides and the like for the sheet of media, but is intended to mean the path that
22 a sheet of media can following in moving through the finishing apparatus 100. Media is
23 moved in initial direction "D" into the media path in the finishing apparatus 100.

24 The finishing apparatus includes a pair of rollers 122 and 124 (which I will call
25 "scoring rollers") which can be used to score, crease or cut the media, as will be
26 explained further below. The finishing apparatus can further include a sheet folding

1 device 130 configured to fold a sheet of media. The sheet folding device 130 can
2 included powered drive rollers 146 and 148 to move the sheet into a first folding position.
3 The folding device 130 further includes a first pinch device, such as pinch roller 132.
4 The pinch roller 132 is configured to operably move from a first position away from the
5 media path to a second position proximate the media path to thereby contact a sheet of
6 media. The folding device also includes a first pair of fold rollers 136 and 148 which are
7 used to fold the sheet of media, as follows. The scoring rollers 122 and 124 are
8 configured to score or crease the media along a crease line (i.e., along an intended fold
9 line), and the pinch roller 132 is configured to move from its first position to its second
10 position and contact the sheet to initiate the folding of the sheet along the crease. The
11 pinch roller 132 urges the crease formed in the sheet towards a first “nip” 134. (The
12 “nip” is the area where the fold rollers 136 and 148 come together.) To form a first fold
13 in a sheet of media, roller 136 rotates in a clockwise direction, and roller 148 rotates in a
14 counter-clockwise direction. The rollers 136 and 148 grasp the sheet at the first crease
15 and fold the sheet into two parts. The folded sheet can then be deposited in a bi-fold
16 receiving compartment 150.

17 The folding device 130 can further include a second pinch roller 142 and a
18 second pair of fold rollers 136 and 138. (Note that for simplicity of construction roller 136
19 forms a part of both the first fold rollers (136, 148) as well as the second fold rollers (136,
20 138), and drive roller 148 also forms a part of the first sheet folding rollers (136, 148).)
21 The components for forming a second fold in a sheet of media operate in a manner
22 similar to the components (132, 136, 148) described above. That is, a second pinch
23 roller 142 moves to contact a second crease formed in a sheet of media and urge the
24 crease towards a second nip 144, which is defined by second fold rollers 136 and 138.
25 The second fold rollers grasp the sheet at the second crease and form a second fold in

1 the sheet to create a tri-fold document. The tri-folded sheet can then be deposited in a
2 tri-fold receiving compartment 140.

3 The sheet folding apparatus 100 can further include sensors 123 (only one of
4 which is shown) to determine the presence of a sheet of media in the media path, as
5 well as the rotary positions of scoring rollers 122 and 124. The sensors can include, for
6 example, edge detectors to detect the absence or presence of a sheet of media in the
7 media path, and thereby allow the processor 58 to determine when a leading edge of a
8 sheet of media enters the scoring rollers 122 and 124. The sensors 123 can also
9 include encoders which can be used to determine the number of rotations of feed rollers
10 (such as rollers 55, 146 and 148), and thus allow the processor 58 to determine the
11 position of a sheet in the media path. The use of such sensors to track the position of a
12 sheet of media in a media path is well known in the art, and need not be discussed
13 further herein. The information from the sensors 123 can be used by the processor 58
14 to direct the operation of the scoring rollers, as well as to operate a sheet folding device
15 actuator (not shown) which is used to actuate the various components of the sheet
16 folding device 130 described above. Specifically, the sensors 123 can be used to
17 determine the location at which the scoring rollers will score or crease a sheet along a
18 contact line (crease line), and this information can then be used by the processor 58 to
19 determine when the contact line is oriented in a preselected position relative to the sheet
20 folding device 130. More specifically, the processor will be able to determine when a
21 crease formed in the sheet is oriented with respect to the pinch rollers 132 and 142 so
22 that the pinch rollers can be moved to contact the sheet at the crease and urge the
23 crease of the sheet into the respective nip (134 or 144). In this way, the functions
24 performed by the sheet finishing apparatus 100 can be performed automatically, as will
25 be further described below.

Turning now to Fig. 5A, first scoring roller 122 of fig. 4 is depicted in sectional front elevation view. The second scoring roller 124 can be configured similar to the first roller 122. The roller 122 is viewed in Fig. 5A from the front, whereas the roller is depicted in a side view in Fig. 4. Thus, media moves in direction "D" (i.e., out of the plane of the paper in which the figure is drawn) to move across the roller 122. The roller 122 is supported by a shaft 153 which can be used to drive the roller in a rotational direction using a drive mechanism such as a motor (not shown). In this way rotation of the roller 122 can be selectively actuated and stopped by connecting the roller drive mechanism to the processor 58 (Fig. 4). The roller 122 includes a body 152 which is defined by an outer surface 155. An elongated slot 154 is formed in the roller body 152 along a substantial portion of the length "L" of the roller. A first knife 156, in the form of an elongated member, is received within the slot 154. The first knife is defined by an edge 158, and is configured to operably move from a first position wherein the edge 158 is retracted away from the surface 155 of the roller 122, to a second position (see Fig. 5B) wherein the edge 158 protrudes outward from the surface 155. In this manner the knife edge 158 can contact a sheet of media moving along the media path "D". As is evident, the edge 158 of the knife 156 is oriented perpendicular to the media path "D". When the edge 158 of the knife 156 contacts the sheet of media, the sheet of media can either be scored (i.e., the edge 158 cuts slightly into the sheet of media), creased (i.e., the edge 158 causes a deformation in the sheet of media along a line coincident with the knife edge), or cut (i.e., the edge severs the sheet of media along the line of contact). I will use the expression "crease" and "score" interchangeably herein, unless expressly stated otherwise. The determination of whether the sheet of media will be creased (deformed), scored or cut will be dependent on (1) the thickness and type of media used for the sheet, (2) the depth to which the knife edge is moved relative to the sheet, (3) any

1 object placed on the opposite side of the sheet and which causes the sheet to be
2 trapped between the knife edge and the object, and (4) the geometry of the knife edge.

3 Figs. 5A and 5B depict one configuration which can be used to deploy the knife
4 156 from the first position (Fig. 5A) to the second position (Fig. 5B). As shown, the
5 roller 122 includes a cam 160 disposed within the elongated slot 154 and in contact with
6 the first knife 156. The cam is configured to slidably move in direction "E" (and in the
7 opposite direction) along a portion of the length "L" of the roller 122. In this way the knife
8 156 can be operably moved from the first position of Fig. 5A to the second position of
9 Fig. 5B. In the position depicted in Fig. 5B, the knife edge 158 can contact a sheet of
10 media and thereby score, crease or cut the sheet. Turning to Fig. 7, a side elevation
11 section view of the roller 122 of Fig. 5B is depicted. The edge 158 of the knife 156 is
12 shown protruding slightly beyond the outer surface 155 of the roller 122. Preferably, the
13 knife 156 is attached to the cam 160 via a slidable connection 159 such that movement
14 of the knife 156 is constrained by the position of the cam 160. This will help prevent the
15 knife 156 from falling into the deployed position when the roller is rotated 180 degrees
16 from the position depicted in Fig. 5A. That is, the connection between the knife 156 and
17 the cam 160 ensures that the knife is selectively deployable, rather than being
18 incidentally deployed when the roller 122 is in a position 180 degrees from that depicted
19 in Fig. 5A.

20 Returning to Fig. 5A, the cam 160 can be connected to a knife actuator 164 via a
21 connecting member 162. For example, knife actuator 164 can be a solenoid which can
22 be used to push the cam 160 from the position depicted in Fig. 5A to the position
23 depicted in Fig. 5B, and likewise to pull the cam from the position depicted in Fig. 5B to
24 the position depicted in Fig. 5A. The connecting member 162 can be configured to
25 freely rotate within the actuator 164, thus allowing the roller 122 to freely rotate.
26 Alternately, the actuator 164 can be supported on a rotatable mounting. As will be more

1 fully described below, the operation of the knife actuator 164 can be controlled by the
2 processor (58, Fig. 4). In this way the knife 156 can be moved to the second position
3 (Fig. 5B) in response to receiving an instruction to form a crease along an intended fold
4 line on a sheet of media moving along the media path "D".

5 Turning now to Fig. 6A, a side elevation view depicts the scoring rollers 122 and
6 124 of Fig. 4. The second roller 124 can be configured similarly to the first roller 122, as
7 described above. That is, the second roller 124 can comprise a knife 170 which is
8 formed from a second elongated member and is received in an elongated slot 171 in the
9 roller. The knife 170 can be moved from a first position (Fig. 6A) to a second position
10 (Fig. 6B) via a cam 172 and an actuator (not shown). Preferably the first roller 122 and
11 the second roller 124 are positioned essentially parallel to one another, and on opposite
12 sides of the media path (as indicated by the sheet of media "M"). In the example
13 depicted in Fig. 6A, the first knife 156 is deployed to contact the first side "S1" of the
14 sheet of media "M". This results in a first crease (such as along fold line 18 of Fig. 1)
15 being formed in the sheet. As seen in Fig. 6A, the edge of the first knife 156 preferably
16 pushes the sheet "M" slightly into the slot 171 of the second roller 124. This facilitates
17 the formation of a more well defined crease than if the sheet were not pushed into the
18 slot 171. Further, the use of the slot 171 in conjunction with the knife 156 reduces the
19 likelihood that the knife 156 will cut the media, which can occur if the edge of the knife
20 156 presses the sheet "M" against a fixed object.

21 As can be seen in Fig. 6B, the second knife 170 can be deployed to contact the
22 second side "S2" of the sheet "M". In this instance the first knife 156 is retracted into the
23 slot 154 of the first roller 122 so that the second knife 170 can preferably push the sheet
24 "M" slightly into the slot 154 of the first roller 122. The action depicted in Fig. 6B results
25 in the formation of a second crease on the sheet (the first crease being formed in the
26 action depicted in Fig. 6A). Preferably, the sheet of media "M" is moved forward in

1 direction "D" (Fig. 6A) between Figs 6A and 6B. In this way the sheet "M" can first be
2 scored or creased at a first crease line (intended fold line) on first side "S1", and later
3 creased at a second crease line (intended fold line) on second side "S2". The
4 subsequently creased sheet can then be folded into the shape of the pamphlet 300
5 depicted in side view in Fig. 12.

6 Preferably, the elongated slot (154, 171, Fig. 6A, and 154, Fig. 7) is relatively
7 narrow at the point where the media is pushed into the slot by the knife in the opposing
8 roller. This facilitates the formation of a more well defined crease in the sheet of media.
9 However, in one variation the slot can be wider, and a surface can be selectively moved
10 into the slot to facilitate processing of the sheet by a knife located in the opposing roller.
11 For example, turning to Fig. 8, a partial side elevation sectional view of a roller 224 is
12 depicted. The roller 224 can be used in place of either, or both, of the rollers 122 and
13 124 of Fig. 6A. The roller 224 is configured to be arranged in a complementary set of
14 rollers, as in the configuration depicted in Fig. 6A for rollers 122 and 124. Thus, roller
15 124 of Fig. 6A can be replaced with roller 224 of Fig. 8, for example. The roller 224 of
16 Fig. 7 includes a knife 256, which can be actuated in a manner similar to the knife 156 of
17 Figs. 5A and 5B. However, as seen by a comparison of Fig. 7 and Fig. 8, the slot 254 in
18 roller 224 (Fig. 8) is considerably wider at the surface of the roller than is the slot 154 in
19 roller 122 (Fig. 7). Roller 224 further includes an anvil device 280. As shown, the anvil
20 device 280 includes a creasing anvil 266 and a cutting anvil 268. The anvil device 280 is
21 disposed within the roller 224 and is operably moveable in direction "C" from a first
22 position away from the elongated slot 254 to a second position in the elongated slot.
23 The anvil device 280 is operably moveable via cam 272, in a manner similar to
24 movement of blade 156 by cam 160, described above with respect to Figs. 5A and 5B.
25 When the knife of the opposing roller (not depicted) is in the second or deployed position
26 (as in Fig. 7), the knife edge can selectively contact one of the two anvils 268 or 270. As

1 can be seen by the detail of Fig. 9, the creasing anvil 278 can include a rounded
2 creasing slot 278, allowing the media to be pushed into the slot 278 with reduced risk of
3 cutting the media. On the other hand, the cutting anvil 268 can include a sharply
4 notched cutting slot 276, configured to receive the edge of the knife in a manner
5 intended to shear a sheet of media placed between the knife and the cutting anvil.
6 When the creasing anvil 270 is disposed in the slot 254 (Fig. 8), then the cutting anvil
7 can be received within an anvil receiving slot 274 in the roller 224. In this way, by
8 adjusting the position of the anvil cam 272, a sheet of media can be selectively either cut
9 or creased by a knife in an opposing roller.

10 It will be appreciated that the sheet finishing apparatus 100 depicted in Fig. 4
11 comprises but one example of an apparatus that can be used to implement the methods
12 of the present invention. Generally, the creasing/cutting knives 156 and 170 can be
13 replaced with a "creasing tool", which is any tool, device or apparatus which can be used
14 to form a crease in, or score, a sheet of media. It is not essential that the creasing tool
15 actually physically contact the sheet. For example, the creasing tool can be a laser used
16 to score the sheet. Also, while the apparatus of the present invention preferably allows
17 the sheet to be moved in the media path while being creased or scored, this is not a
18 requirement. For example, the creasing tool can comprise a press used to move a
19 creasing knife towards the sheet of media as the sheet is temporarily paused in the
20 media path. However, preferably the creasing tool is configured to be deployed in a
21 manner which allows forward progress of the sheet within the media path to be
22 continuous.

23 The creasing tool can be actuated by a "creasing tool actuator", being any device
24 which will cause the creasing tool to form the crease in the sheet of media. For
25 example, if the creasing tool is a knife pressed against the sheet, then the actuator can
26 be a mechanical actuator, such as a cam, or an electro-mechanical actuator, such as a

1 solenoid, a stepper motor, a linear motor, an electromagnet, or any other electro-
2 mechanical positioning device. The actuation of the creasing tool actuator can be
3 selectively performed (such as by a controller), or passively performed (such as by a
4 cam arrangement which periodically actuates the actuator). Certain electro-mechanical
5 actuators allow precise positioning of the creasing tool so that the creasing tool can form
6 a crease in the sheet without cutting the sheet, and can score the sheet without cutting
7 through the sheet. Precision position devices used as the creasing tool actuator also
8 sheets of media of various media thicknesses to be accommodated.

9 As another example of how the sheet finishing apparatus 100 can be modified,
10 fold rollers (136, 138, 148) do not necessarily need to be used to fold the sheet. For
11 example, the fold rollers can be replaced with a folding plane, such as a hinged metal
12 plate, on which at least a portion of the sheet is placed after the crease is formed in the
13 sheet. The crease can be positioned at a hinged joint in the folding plane so that the
14 folding plane folds the sheet at the crease. Accordingly, it is proper to describe the fold
15 rollers 136, 138, 148 as but one form of a "sheet folding device", being any device which
16 can be used to fold a sheet of media along a crease.

17 Fig. 15 depicts a side elevation view of one alternate configuration 500 of a pair
18 of scoring rollers 522 and 524 which can be used to implement the methods of the
19 present invention. First scoring roller 522 includes a knife 556 which is biased away
20 from an opening in the roller by spring 554. Likewise, second scoring roller 524 includes
21 a knife 570 which is biased away from an opening in the roller by spring 568. As can be
22 seen, each of the rollers 522 and 524 are eccentric, so that as the rollers rotate in
23 counter-rotating directions, they come together about the media path "D". First roller 522
24 includes a cam 560 which can be rotated to the position depicted to deploy the first knife
25 556 to thereby score or crease the first side of a sheet of media moving along the paper
26 path "D". Second scoring roller 524 is likewise provided with a cam 572 which can be

1 used to deploy the knife 570. However, in the position depicted in Fig. 15, cam 572 is
2 positioned such that knife 570 is not deployed. In order to score or crease the second
3 side of the sheet of media, cam 572 can be rotated ninety degrees from the position
4 depicted to thereby push knife 570 into the opening near the surface of the roller 524.
5 When a sheet is not to be scored or creased for folding, then cam 560 can be rotated
6 ninety degrees from the position shown such that knife 556 is in a retracted position.
7 Cams 560 and 572 can be rotated using a solenoid or the like as a knife actuator.

8 I will now describe, with reference to Fig. 4 and Figs. 10A through 10J, one
9 example of how the document processing apparatus of Fig. 4 can be used to fold a
10 sheet of media. Figs. 10A through 10J depict only the sheet finishing apparatus 100 of
11 the document processing apparatus 80 of Fig. 4. In order to simplify the depiction of the
12 operation of the document processing apparatus 100, in Figs. 10A through 10J the
13 lengths of sections of media "M" passing through the different portions of the apparatus
14 100 are not to drawn to scale, nor are they consistently depicted in length from figure to
15 figure.

16 As seen in Fig. 4, the scoring rollers 122 and 124 are slightly retracted away from
17 one another along the paper path "D". In Fig. 10A, the scoring rollers have been brought
18 together. This can be performed using any known device for deploying and retracting
19 rollers, such devices being well understood in the art. In the position depicted in Fig.
20 10A, roller 122 rotates in a clockwise direction, and roller 124 rotates in a counter-
21 clockwise direction (see respective direction arrows R and R', Fig. 6A). The scoring
22 rollers 122 and 124, along with the drive rollers 146 and 148, move the sheet "M" in
23 direction "D". As shown in Fig. 10B, the first knife 156 contacts the upper side of the
24 sheet "M", forming a first crease in the sheet along a first crease line "C1", which is
25 indicated in Fig. 10C, wherein the sheet "M" has moved further along the media path "D".
26 At Fig. 10D the crease line C1 is aligned with the first pinch roller 132. Preferably, at this

1 point the scoring rollers 122 and 124 are retracted from the media, although this is not a
2 requirement. As also indicated, the first knife 154 has been retracted into the elongated
3 slot in the first roller 122.

4 Once the first crease line C1 is aligned with the first pinch roller 132, as indicated
5 in Fig. 10D, the drive rollers 146 and 148 can be stopped to halt forward progress of the
6 sheet of media "M" in the media path, although this is not a requirement, and the
7 process can be continued without halting forward progress of the sheet. At Fig. 10 E the
8 first pinch roller 132 is deployed to urge the sheet "M", at the first crease line "C1", into
9 the first nip 134. The first fold rollers 136 and 148 are then rotated in respective
10 clockwise and counter-clockwise directions to grasp the sheet at the first crease line C1,
11 as depicted in Fig. 10F, and move the sheet in direction "F1". This results in the sheet
12 "M" being folded into a first portion "P1" and a second portion "P2" about the crease line
13 "C1. At this point, the fold rollers 136 and 148 can be used to direct the bi-folded sheet
14 "M" into the bi-fold sheet container 150. However, additional folds can also be formed in
15 the sheet, as will now be described.

16 In order to fold the sheet "M" into a tri-fold sheet, such as pamphlet 300 of Fig.
17 12, at Fig. 10F the second knife 170 in roller 124 is deployed, and the rollers 122 and
18 124 are brought together about the sheet of media "M". Note that the knife 156 in roller
19 122 is retracted at this point. The scoring rollers 122 and 124 are then rotated in
20 respective clockwise and counter-clockwise directions to form a second crease along a
21 second crease line "C2" (not shown) in the lower side of the sheet "M" as the sheet is
22 moved forward in the media path, as indicated at Fig. 10G. The second crease line "C2"
23 is then moved, via drive rollers 146, 148 and 136, to a position where the second crease
24 line is aligned with the second pinch roller 142, as depicted in Fig. 10H. At this point the
25 second pinch roller 142 is moved from the position indicated in Fig. 10G to the position
26 shown in Fig. 10H, to thereby urge the second crease "C2" into the second nip 144

1 between second fold rollers 136 and 138. The second fold rollers 136 and 138 are then
2 rotated in respective clockwise and counter-clockwise directions to grasp the sheet at
3 the second crease line "C2" and move the sheet "M" in direction "F2", as depicted in Fig.
4 10I. This results in the sheet "M" being folded into a tri-fold pamphlet. For example, at
5 Fig. 12, the pamphlet 300 is folded into a first portion 301 and a second portion 303 by
6 folding the second portion towards the first portion in direction F1 (as in Fig. 10F) at the
7 first crease 304. The third portion 305 of the sheet "M" is then folded towards the first
8 and second portions 301 and 303 of the sheet in the direction "F2" (Fig. 10I) at the
9 second crease 302 to form a Z-shaped tri-fold pamphlet. The pamphlet can then be
10 deposited in the tri-fold container 140, as depicted at Fig. 10J, using rollers 136 and 138.

11 As can be observed by viewing the sequence of sheet creasing depicted in Figs.
12 10A and 10B, at the creasing location (i.e., the location in the sheet finishing apparatus
13 100 of Fig. 4 where the sheet is creased) the sheet of media "M", and the creasing knife
14 156, are simultaneously moved to the creasing location. That is, the sheet finishing
15 apparatus 100 allows a sheet of media to be advanced in the media path while
16 simultaneously being creased. This is advantageous since the apparatus does not
17 require forward movement of the sheet to be stopped while the crease is formed, thus
18 reducing the time required to form the folded sheet.

19 As can be seen, the sheet folding apparatus 100 of Fig. 4 can be used to fold a
20 sheet of media into several different pamphlet shapes. For example, with reference to
21 Fig. 13, a generally "U" shaped pamphlet 310 can also be formed. Specifically, a first
22 crease 313 is formed in the bottom side of the sheet of media "M" as per Fig. 10G. The
23 sheet "M" is then folded about the crease 313 in direction "F11" into a first portion 312
24 and a second portion, as per Figs. 10H and 10I. A second crease 315 (Fig. 13) is then
25 formed in the bottom side of the sheet "M", also per Fig. 10G, to thereby define a third
26 portion 316 of the sheet "M" (Fig. 13). The third portion 316 is then folded in direction

1 "F12" (also as per Figs. 10H and 10I) onto the first and second portions (312 and 314,
2 respectively) to form the final pamphlet 310. In the example depicted in Fig. 13, the
3 three portions (312, 314 and 316) of the sheet "M" are of approximately equal length. A
4 similar process can be used to form the pamphlet 320 of Fig. 14. However, the
5 pamphlet 320 of Fig. 14 has a first portion 321 and a third portion 325 of sheet "M" which
6 are of equal length, while the second portion 323 is twice the length of each of the first
7 and third portions. This can be accomplished merely by changing the location of the
8 creases 322 and 324 along the sheet. Functionally, this can be performed by using the
9 processor 58 and sensors 123 (Fig. 4), along with input from a user (for example, via
10 user input points 65), to identify the locations at which the creases are to be formed in
11 the sheet, and the final desired geometry of the sheet after folds "F" are formed in the
12 sheet "M".

13 To effect essentially automatic implementation of the methods of the present
14 invention, a sheet folding/trimming program (62, Fig. 4) can be used by a processor 58.
15 Specifically, the sheet folding/trimming program 62 can be executed by the processor 58
16 in order to deploy the knives (156, 170, Figs. 6A and 6B) and the pinch bars (132, 142,
17 Fig. 4), as well as the activation and non-activation of the drive rollers and fold rollers
18 (146, 148, 136, 138), to crease or score, and fold, a sheet of media. That is, the
19 sequence of knife deployment and roller activation depicted in Figs. 10A through 10J
20 can be performed automatically, as directed by the sheet folding/trimming program 62
21 and as executed by the processor 58. Fig. 11 depicts one example of steps of a flow
22 chart 400 which can be reduced to computer executable steps to form the sheet
23 folding/trimming program 62. It will be appreciated that the program 62 can be used only
24 to actuate the sheet creasing tool actuator, and does not necessarily need to also control
25 the folding of the sheet by the sheet folding device. In this case, the program 62 can be

described as a "sheet creasing program." However, the following example assumes that the operation of the sheet folding device is also controlled by the program 62.

With respect to Fig. 11, at step 402 a sheet folding program is initiated as directed by a user, via a user console 64 (Fig. 4), or via a computer (not shown) connected to the sheet finishing apparatus 100. When the sheet folding program is not implemented, then a sheet of media is imaged (as for example, by the imaging apparatus 50 of Fig. 4) but is not folded. Assuming, however, that a user desires a sheet of media to be folded, then at step 404 the processor determines the size of the sheet of media (using sensors or the like, or from a user identified sheet size), and recalls a pre-defined sheet length "SL" from a memory device, such as memory 59 of Fig. 4. For example, if a user indicates that the sheet to be used is a size A4 sheet, then the processor can determine that the sheet length is approximately 297 mm in length. Alternately, a user can designate a sheet length "SL" at this point. At step 406 the processor then reads the number of folds "n" to be formed in the sheet. The number of folds "n" is typically designated by a user using an input console, such as console 64 of Fig. 4. This information can be stored in the RAM memory 60 and accessed by the processor 58. This information can also include the final geometry of the folded sheet, as for example indicated by Figs. 12-14 which indicate three different geometries of tri-folded sheets.

At step 408 the processor determines the positions "K" at which creases (and thus folds) are to be formed in the sheet. This process is performed as long as the positions at which the creases are to be formed is less than, and not equal to or greater than, the length of the sheet. That is, creases are formed at positions $X = K (L / (n + 1))$. For example, if the number of folds "n" to be formed in the sheet is one (1), then $K = 1$, and creases are to be formed a single crease location located at distance $X = L / (1 + 1)$, or $L/2$, on the sheet. If two (equidistant) folds are to be formed in the sheet, then $n = 2$,

1 and folds are to be formed at locations $X = 1 L / (2 + 1)$ and $X = 2 L / (2 + 1)$ (i.e., at
2 locations $X = L / 3$ and $X = 2 L / 3$). After the crease/fold locations are determined at
3 step 408, then, at step 410, the final shape (geometry) of the folded document is
4 determined by accessing the fold-shape information from the random access memory
5 (60, Fig. 4). The sheet folding geometry can be selected by a user, for example via the
6 input console 64 of Fig. 4. For example, the user can select a simple bi-fold sheet, and
7 can also select in which direction the sheet is to be folded (i.e., folded inwards with
8 respect to a designated side of the sheet, or outwards with respect to a designated side).
9 Likewise, a user can select one of the tri-fold sheet configurations depicted in Figs. 12-
10 14, or any other folding configuration. The location of the creases/folds (step 408) and
11 the geometry of the final folded document (step 410) will allow the processor (58, Fig. 4)
12 to determine which knives (156 and/or 170, Fig. 6A) are to be deployed, as well as the
13 locations (e.g., C1 (Fig. 10C) and C2 (Figs. 10G and 10H)) at which the knives are to be
14 deployed, as initiated at step 412.

15 At step 414 the first knife (as determined by the fold geometry at step 412) is
16 deployed to form the first crease at fold location $X = K (L / (n + 1))$, as described above.
17 The sheet of media is then moved along the media path at step 416 to the appropriate
18 fold roller (e.g., rollers 136 and 148 of Fig. 4), and the first fold is formed in the sheet, as
19 described above with respect to Figs. 10A through 10F. Subsequent folds (if any) are
20 formed in the sheet by first the creasing the sheet with the appropriate knife (step 418)
21 and then using the appropriate fold rollers to form the fold (step 420). The final folded
22 sheet is then deposited in the appropriate sheet receptacle at step 422, and the sheet
23 folding program ends at step 424.

24 It is understood that the flow chart 400 depicted in Fig. 11 is exemplary only, and
25 that additional or different steps can be used to equal effect. It will also be appreciated
26 that, depending on the selected geometry of the final folded sheet, and the spacing of

1 the scoring rollers (122, 124, Fig. 4) with respect to the pinch rollers (132, 142) and the
2 fold rollers (136, 138, 148), the steps of the flowchart 400 (Fig. 11) can be performed in
3 a different order than that depicted. For example, step 416 in Fig. 11 indicates that the
4 first fold is formed prior to making the next crease at step 418. However, if the next
5 crease is formed by the scoring rollers before the first crease has advanced to the first
6 pinch roller (132), then step 418 ("form next crease") will be performed before step 416
7 ("make first fold").

8 The present invention also provides a method of automatically folding a sheet of
9 media. The method includes forming a first crease on a sheet of media along a first
10 crease line. The first crease defines first and second portions of the sheet. For
11 example, with respect to Fig. 12, a first crease line 302 defines the sheet of media "M"
12 into a first portion 301, and a second portion comprised of portions 303 and 305. In the
13 method, the sheet is next urged towards a nip (such as nip 134, Fig. 4) by pressing the
14 sheet of media essentially along the first crease while supporting the first and second
15 portions of the sheet. This step is similar to the step depicted in Fig. 10E wherein the
16 first pinch roller 132 is urging the sheet "M" towards the nip 134 between rollers 138 and
17 148. At the nip, the sheet is grasped at essentially the first crease line, and the first
18 portion of the sheet is urged towards the second portion of the sheet. This step can be
19 performed as indicated in Fig. 10F, wherein the fold rollers 136 and 148 are used to fold
20 the sheet into the two portions along the crease line. The method can further comprise,
21 prior to forming the first crease, heating the elongated creasing member.

22 The method can further include forming a second crease on the sheet of media
23 along a second crease. The second crease line thus defines a third portion of the sheet
24 defined by the second crease line. For example, the sheet of media "M" in Fig. 12 is
25 creased along second crease line 304 to thereby define the third portion of the sheet
26 305. The sheet is then urged towards a second nip (e.g., nip 144, Fig. 4) by pressing

1 the sheet of media essentially along the second crease while supporting at least one of
2 the first and second portions of the sheet (see for example Fig. 10H), and also
3 supporting the third portion of the sheet. At the second nip, the sheet is grasped at
4 essentially the second crease line and the third portion of the sheet is urged towards the
5 first and second portions of the sheet (see for example Fig. 10I). In this way a tri-fold
6 sheet, such as any of the sheets "M" depicted in Figs. 12, 13 and 14, can be formed.

7 The geometry of the final folded sheet will dictate which side (or sides) of the
8 sheet are to be scored or creased, and the particular components of the folding device
9 (130, Fig. 4) to be employed to form the final folded sheet. For example, in order to form
10 a "Z" folded sheet, such as sheet 300 of Fig. 12, the first crease 302 can be formed by
11 pressing a first elongated member (such as knife 156, Fig. 6A) against the first side
12 ("S1", Fig. 12) of the sheet "M", and the second crease 304 is formed by pressing a
13 second elongated member (such as knife 170, Fig. 6A) against the second side of the
14 sheet. This corresponds to the sequential steps depicted in Figs. 6A and 6B.

15
16 While the above invention has been described in language more or less specific
17 as to structural and methodical features, it is to be understood, however, that the
18 invention is not limited to the specific features shown and described, since the means
19 herein disclosed comprise preferred forms of putting the invention into effect. The
20 invention is, therefore, claimed in any of its forms or modifications within the proper
21 scope of the appended claims appropriately interpreted in accordance with the doctrine
22 of equivalents.